

Rhenus Greases for Trucks and Busses

Application	Product Name	Structure	Approvals	Remarks
wheel bearing				
wheel bearing	rhenus LKA 2	Li-comp-soap, NLGI 2, v ₄₀ = 170, semi synthetic -30 to 150 °C	MB 265.1; MAN 284, Volvo 1277,18 + 1277,2	suitable for 400.000 km street traffic
	rhenus LKR 25	Li-comp-soap, NLGI 2-3, v ₄₀ = 210, semi synthetic -30 to 150 °C	MB 265.1; MAN 284, Volvo 1277,18 + 1277,2	suitable for 700.000 km street traffic
	rhenus LKI 2	Li-comp-soap, NLGI 2, v ₄₀ = 200, synthetic -40 to 150 °C	Special development	suitable for 1.500.000 km street traffic
central lubrication system	rhenus LJU 02 GR	Li-soap, NLGI 00/000, v ₄₀ = 45, mineral oil -50 to 120 °C	MB 264; MAN 283; SKF/Willy Vogel, Lincoln, Tecalemit, Baier&Köppel	suitable for central lubrication system on truck for several lubricant points in the requested NLGI class
	rhenus LMN 2	Li-soap, NLGI 2, v ₄₀ = 110, mineral oil -30 to 130 °C	MB 267; MAN 283 BEKA-MAX, Lincoln, Delimon	
5 wheel grease	rhenus LBH 2	Li-soap, NLGI 2, v ₄₀ = 155, mineral oil -30 to 130 °C graphite + MoS ₂		standard grease
	rhenus AKG 2	Al-comp-soap, NLGI 2, v ₄₀ = 570, mineral oil -20 to 300 °C graphite + active EP additives		special grease for longer service lifes